

# KT8-40

### Circular Chart Recorder



#### **FEATURES**

- Display
- Audible Alarms
- Platinum RTD Replaceable Sensor™


#### **ABOUT**

8" (203mm) chart recorders offer the largest resolution out of any chart recorders.

All chart recorders feature a large 8" chart and user-selectable recording time-frames and ranges.

These units are compatible with Dickson's Replaceable Sensors™, making calibrating your chart recorder easier than ever.





#### For more information, please refer to

T: +31 (0)174 287 160
E: info@vrsupplies.com
W: www.vrsupplies.com



## KT8-40

-

### Circular Chart Recorder

### **Specifications**

- Alarm Type: Audio/Visual
- Ambient Operating RH Conditions: 0-95% RH non-condensing
- Ambient Operating Temperature Conditions: 32°F to 120°F (0°C to 50°C)
- Battery Backup: (4) C Batteries
- Battery Life: 1 Month (Avg)
- Calibration Options: N100, N300, N400
- Channels: CH1: Temperature
- Chart Rotation Speed: 24 Hour, 7 Day
- Dimensions LxWxH: 9 3/8"x2 3/4"x10 1/8"
- Display Dimensions: 5 1/8" x 1"
- Display Type: LCD
- Enclosure: Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial
- IP Rating: IP20
- Included Accessories: AC Adapter, Red Pen, Blue Pen, (4) C Batteries, Quick Start Guide and Replaceable Sensor™ \*Charts sold separately
- Mounting Options: Free Standing or Wall Mount (With Keyhole)
- Power Cord: 6 ft
- Power Source: 120 to 240 VAC, 12 VDC (INTL fittings available); AC Adapter
- Power Status Indicator: LED Indicator
- Unit Weight: 2.45lbs without batteries
- Warranty: 12-Month Limited
- Replaceable Sensor SKU: RS040
  - REPLACEABLE SENSOR™ SPECIFICATIONS:

Temperature Accuracy ±0.5°F from -148°F to 350°F (± 0.3°C from -100°C to 176°C)

Temperature Range -148°F to 350°F (-100°C to 176°C)