

KT8-50

-

•

.

8

-

1

-

0

.

100

Circular Chart Recorder



ABOUT


8" (203mm) chart recorders offer the largest resolution out of any chart recorders.

All chart recorders feature a large 8" chart and user-selectable recording time-frames and ranges.

These units are compatible with Dickson's Replaceable Sensors[™], making calibrating your chart recorder easier than ever. **FEATURES**

- Display
- Audible Alarms
- Ambient Temperature Replaceable Sensor[™]





For more information, please refer to

T: +31 (0)174 287 160 E: info@vrsupplies.com W: www.vrsupplies.com



KT8-50

Circular Chart Recorder

S	pecifications
•	Alarm Type: Audio/Visual
•	Ambient Operating RH Conditions: 0-95% RH non-condensing
•	Ambient Operating Temperature Conditions: 32°F to 120°F (0°C to 50°C)
•	Battery Backup: (4) C Batteries
•	Battery Life: 1 Month (Avg)
•	Calibration Options: N100, N300, N400
•	Channels: CH1: Temperature
•	Chart Rotation Speed: 24 Hour, 7 Day
•	Dimensions LxWxH: 9 3/8"x2 3/4"x10 1/8"
•	Display Dimensions: 5 1/8" x 1"
•	Display Type: LCD
•	Enclosure: Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial
•	IP Rating: IP20
•	Included Accessories: AC Adapter, Pen(s), (4) C Batteries, Quick Start Guide, Replaceable
	Sensor [™] . *Charts sold separately
•	Mounting Options: Free Standing or Wall Mount (With Keyhole)
•	Power Cord: 6 ft
•	Power Source: 120 to 240 VAC, 12 VDC (INTL 昀椀 ttings available); AC Adapter
•	Power Status Indicator: LED Indicator
•	Unit Weight: 2.45lbs without batteries
•	Warranty: 12-Month Limited
•	Replaceable Sensor SKU: RS050
	REPLACEABLE SENSOR™ SPECIFICATIONS:
	Temperature Accuracy: =+/-1.2°F from 20°F to 122°F (+/-1°C from -30°C to 50°C)
	Temperature Range: -22°F to 122°F (-30°C to 50°C)
	•
	•
	•
	•
	•
	•
	•
	•
	•