

TH8-10

•

-

.

.

Circular Chart Recorder



ABOUT

8" (203mm) chart recorders offer the largest resolution out of any chart recorders.


All chart recorders feature a large 8" chart and user-selectable recording timeframes and ranges.

These units are compatible with Dickson's Replaceable Sensors[™], making calibrating your chart recorder easier than ever.

FEATURES

- Display
- Audible Alarms
- Ambient Temperature and Humidity Replaceable Sensor™





For more information, please refer to

T: +31 (0)174 287 160 E: info@vrsupplies.com W: www.vrsupplies.com



TH8-10

Circular Chart Recorder

Specifications	
	Alarm Type: Audio/Visual
	Ambient Operating RH Conditions: 0-95% RH non-condensing
	Ambient Operating Temperature Conditions: 32°F to 120°F (0°C to 50°C)
	Battery Backup: (4) C Batteries
	Battery Life: 1 Month (Avg)
	Calibration Options: N100, N300, N400
	Channels: CH1: Temperature CH2: Humidity
	Chart Rotation Speed: 24 Hour, 7 Day
	Dimensions LxWxH: 9 3/8"x2 3/4"x10 1/8"
	Display Dimensions: 5 1/8" x 1"
	Display Type: LCD
	Enclosure: Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial
	IP Rating: IP20
	Included Accessories: AC Adapter, Red Pen, Blue Pen, (4) C Batteries, Quick Start Guide and
	Replaceable Sensor™ *Charts sold separately
•	Mounting Options: Free Standing or Wall Mount (With Keyhole)
•	Power Cord: 6 ft
•	Power Source: 120 to 240 VAC, 12 VDC (INTL fittings available); AC Adapter
•	Power Status Indicator: LED Indicator
•	Unit Weight: 2.45lbs without batteries
•	Warranty: 12-Month Limited
•	Replaceable Sensor SKU: RS010
	REPLACEABLE SENSOR™ SPECIFICATIONS:
	Humidity Accuracy: ±2.0% RH from 5% to 95% RH
	Temperature Accuracy: ±0.8°F (±.44C) from 20°F to 122°F ±1.8°F (±1°C) remaining range
	Temperature Range: 32°F to 120°F (0°C to 50°C)
	•
	•
	•
	•
	•
	•
	•