

TH8-11R

Circular Chart Recorder



FEATURES

- Display
- Audible Alarms
- Extension Cable
- Relays
- Ambient Temperature and Humidity
 Replaceable Sensor™


ABOUT

8" (203mm) chart recorders offer the largest resolution out of any chart recorders.

All chart recorders feature a large 8" chart and user-selectable recording time-frames and ranges.

These units are compatible with Dickson's Replaceable Sensors™, making calibrating your chart recorder easier than ever.





For more information, please refer to

T: +31 (0)174 287 160
E: info@vrsupplies.com
W: www.vrsupplies.com



TH8-11R

-

Circular Chart Recorder

Specifications

- Alarm Type: Audio/Visual/Relay on High/Low Limits
- Ambient Operating RH Conditions: 0-95% RH non-condensing
- Ambient Operating Temperature Conditions: 32°F to 120°F (0°C to 50°C)
- Battery Backup: (4) C Batteries
- Battery Life: 1 Month (Avg)
- Calibration Options: N100, N300, N400
- Channels: CH1: Temperature, CH2: Humidity
- Chart Rotation Speed: 24 Hour, 7 Day
- Dimensions LxWxH: 9 3/8"x2 3/4"x10 1/8"
- Display Dimensions: 5 1/8" x 1"
- Display Type: LCD
- Enclosure: Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial
- IP Rating: IP20
- Included Accessories: AC Adapter, Red and Blue Pens, (4) C Batteries, Quick Start Guide, Replaceable Sensor™, Ext. Cable. *Charts sold separately
- Mounting Options: Free Standing or Wall Mount (With Keyhole)
- Power Cord: 6 ft
- Power Source: 120 to 240 VAC, 12 VDC (INTL 昀椀ttings available); AC Adapter
- Power Status Indicator: LED Indicator
 The Control of the
- Unit Weight: 2.45lbs without batteries
- Warranty: 12-Month Limited
- Replaceable Sensor SKU: RS010

REPLACEABLE SENSOR™ SPECIFICATIONS:

Humidity Accuracy: ±2.0% RH from 5% to 95% RH

Temperature Accuracy: ±0.8°F (±.44C) from 20°F to 122°F ±1.8°F (±1°C) remaing range

Temperature Range: -40°F to 185°F (-40°C to 85°C)